


REMARKS

The specification and drawings have been amended in accordance with U.S. practice. New patent claims are presented based on the PCT prosecuted claims 1-38. The remaining PCT prosecuted claims are being
5 presented in two additional divisional applications being filed after the Serial Number is received in this parent national stage filing.

An Information Disclosure Statement is enclosed.

Respectfully Submitted,

10

 (Reg. 27,841)
Schiff, Hardin LLP

CUSTOMER NO. 26574

15

Patent Department
6600 Sears Tower
233 South Wacker Drive
Chicago, Illinois 60606
Telephone: 312/258-5786
Attorneys for Applicant.

20

CH1\ 4442055.1

IN THE DRAWINGS:

Enclosed are Replacement Sheets in which legends have been added in Figures 6, 7 and 8. Figures 6, 7, and 8 are the translated drawings attached to the translation of the PCT document. Lead lines were also added
5 with the legends, and arrows were placed for lead lines from reference numerals 100, 200, and 300. No new matter is added.

-1- IAP20 Rec'd PCT/PTO 19 JAN 2006

SPECIFICATION**TITLE****"DEVICE AND METHOD FOR ELECTROPHORETIC LIQUID DEVELOPMENT"**

5

BACKGROUND

For single- or multi-colored printing of a recording medium (for example a single sheet or a belt-shaped recording medium made from the most varied materials, for example paper or thin plastic or metal films), it is known to
10 generate image-dependent potential images (charge images) on a potential image medium, for example a photoconductor, which image-dependent potential images correspond to the images to be printed that are comprised of regions to be inked and regions that are not to be inked. The regions to be inked (called image positions in the following) of the potential images are
15 made visible with a developer station (inking station) via toner. The toner image is subsequently transfer-printed onto the recording medium (also called printing substrate or final image medium).

Either dry toner or liquid developer containing toner can thereby be used to ink the image positions.

20 A method for electrophoretic liquid development (electrographic development) in digital printing systems is, for example, known from EP 0 756 213 B1 or EP 0 727 720 B1. The method described there is also known under the name HVT (High Viscosity Technology). A carrier liquid containing silicon oil with ink particles (toner particles) dispersed therein is thereby used
25 as a liquid developer. The toner particles typically have a particle size of less than 1 micron. More detail in this regard can be learned from EP 0 756 213 B1 or EP 0 727 720 B1, which are a component of the disclosure of the present application. Electrophoretic liquid development methods of the cited type with silicon oil as a carrier liquid with toner particles dispersed therein are
30 described there, in addition to a developer station made from one or more developer rollers for wetting of the image carrier element with liquid developer corresponding to the potential images on the image carrier element. The

developed potential image is then transferred onto the recording medium via one or more transfer rollers.

~~The problem generally forming the basis of the invention~~ A problem is to specify a device and a method for electrophoretic liquid development, whereby the general problem comprises various aspects that are divided up in the following into three individual problems[.];

a) ~~The~~ A first problem to be solved ~~by the invention~~ is to specify a device and a method with which the feed of the liquid developer to the image carrier element is simplified[.];

10 b) A second problem to be solved is to specify a modularly-designed printing device with which a printing system can be achieved for the most varied, complex printing machines for professional, digital high-speed printing; and

15 c) A third problem to be solved is to specify an electrophotographic printing device and a method with which a variable speed can be realized given constant print quality.

SUMMARY

In a method or device for transport of liquid developer to an image carrier element for electrophoretic digital printing, a developer unit is arranged adjacent to the image carrier element, the developer unit directing a liquid developer comprising toner particles to the image carrier element, the toner particles crossing over to the image carrier element corresponding to previously-generated potential images. A raster unit is arranged adjacent to the developer unit. The raster unit transports the liquid developer to the developer unit by use of a raster. An electrical voltage is applied between the raster unit and the developer unit in order to exert a targeted field effect on the toner particles in a direction towards the developer unit. A chamber scraper comprising a dosing scraper is arranged adjacent to the raster unit and having liquid developer comprising said toner particles which are already charged.

20

25

30 From the chamber scraper the raster unit accepts the liquid developer via the dosing scraper. The chamber scraper is arranged and operable such that the dosing scraper is washed over by the liquid developer.

~~This problem is solved via a device according to the features of the claim 1 and via a method according to claim 38.~~

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a representation of the developer station given a first position relative to the image carrier element;

Fig. 2 is a representation of the developer station given a second position relative to the image carrier element;

Fig. 3 is a representation of the developer station given a third position relative to the image carrier element;

10 Fig. 4 is a representation of the developer station given a different arrangement of the chamber scraper relative to the raster roller;

Fig. 5 is a representation of print modules with developer stations around a recording medium;

15 Fig. 6 shows a single printing group that can be combined with a printing device as a module;

Fig. 7 shows a printing device for printing of endless printing substrate webs; and

Fig. 8 shows a printing device for printing of individual sheets (cut sheet).

20 **DESCRIPTION OF THE PREFERRED EMBODIMENT**

For the purposes of promoting an understanding of the principles of the invention, reference will now be made to the preferred embodiment illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended, such alterations and further modifications in the illustrated device, and/or method, and such further applications of the principles of the invention as illustrated therein being contemplated as would normally occur now or in the future to one skilled in the art to which the invention relates.

Advantages of the invention preferred embodiment are:

- 30 - the flexible use and/or arrangement of a chamber scraper within the device (developer station);

- the device is suitable for application in the field of (digital) electrostatic (electrophoretic) printing methods;
- the compact design of the device, for example as a significant component of a compact printing group; and
- 5 - a device that is identical given various installation positions in a printing device, ~~and therewith enables~~ thus enabling variable printer configurations.

In order to ensure a bubble free [sic] transport of the liquid developer, it is appropriate to arrange the chamber scraper such that the dosing scraper is
10 overflowed by liquid developer. The same result is achievable when the liquid developer is exposed to an over-pressure in the chamber scraper, such that the dosing scraper is overflowed by liquid developer.

In order to remove liquid developer exhibiting the inverse residual image from the developer ~~means~~ unit, a cleaning device that accepts the
15 residual image can be arranged adjacent to the developer ~~means~~ unit. The cleaning device can comprise a cleaning roller and a cleaning element (for example a scraper) that strips the liquid developer from the cleaning roller.

The developer ~~means~~ unit can be a developer belt, preferably a developer roller. The raster ~~means~~ unit is preferably a raster roller, however
20 can also be a raster belt.

The quantity of the liquid developer transported to the developer roller can be influenced in a simple manner via the rastering of the raster roller. It is advantageous when the raster roller exhibits a rastering that enables the transport of a volume of liquid developer of 1 to 40 cm³/m² (with regard to the
25 roller surface), advantageously 5-20 cm³/m². The transport of the liquid developer via the raster roller is ~~thereby~~ thus relative to the surface and ~~therewith~~ thus independent of the print speed, such that the same quantity of liquid developer per areal unit is always directed to the developer roller given different printing speeds.

30 It is advantageous that the developer roller, raster roller and cleaning roller can rotate with constant speed ratios (surface velocities), advantageously in the ratio of 1:1:1. The movement directions of the surfaces

of developer roller and image carrier element can ~~thereby~~ thus be in the same direction or in opposing directions, the developer roller and raster roller can rotate in the same direction or in opposing directions, and the developer roller and cleaning roller can rotate in the same direction or in opposing directions.

5 In order to advantageously influence the transfer of liquid developer, a potential for specific field effect on the charged toner particles can be respectively applied at the developer roller and the image carrier element. This also applies between developer roller and cleaning roller as well as between raster roller and developer roller.

10 In order to furthermore advantageously influence the transition of liquid developer, it is appropriate to provide the developer roller with an elastic coating in order to achieve defined effective zones with regard to the adjacent elements. The effective zone is then created via a defined deformation of the elastic coating of the developer roller, advantageously via elastic force feed to
15 the adjacent elements (image carrier element; cleaning roller; raster roller). An effective zone is also created by the incompressible layer of the liquid developer that establishes the separation between developer roller and image carrier element, developer roller and cleaning roller, and developer roller and raster roller.

20 The chamber scraper can comprise one chamber sitting on the circumferential surface of the raster roller, two scrapers sealing the chamber – a closing scraper at the entrance of the chamber (viewed in the rotation direction of the raster roller), a dosing scraper at the exit of the chamber (viewed in the rotation direction of the raster roller) – and two seals laterally
25 applied on the side boundary of the raster roller. The feed of the liquid developer into the chamber can occur via one or more inlet openings, advantageously via pumping; the removal of the liquid developer from the chamber can occur via inlet or outlet openings, whereby the inlet or outlet openings should be exchangeable depending on the installation position
30 relative to the raster roller.

To prevent the inclusion of air bubbles in a disadvantageous installation position, (for example the dosing scraper lies above the closing

scraper in the direction of gravitational pull) and in order to be able to process higher-viscosity liquid developer (for example 1000 mPa*S), a lighter over-pressure can be generated in the chamber.

5 It is advantageous that the installation position of the chamber scraper on the raster roller is executed variably. The installation position of the cleaning direction on the developer roller can likewise be executed variably.

The use of the device as a developer station in an electrophoretic printing device is particularly advantageous. It is then particularly advantageous that the developer roller, the raster roller and the cleaning roller 10 can be arranged at a constant angle relative to one another, such that the arrangement of the developer station is possible at various angular positions around, for example, a roller-shaped image carrier element without changing the association of developer roller, raster roller, cleaning roller relative to one another (i.e. developer stations of the same design can be arranged without 15 alteration at different positions along the image carrier element). This advantage is increased further in that the angular position of the chamber scraper on the raster roller can be varied.

Printing modules can ~~therewith~~ thus be achieved that respectively comprise a developer station and an image carrier element that can be 20 arranged at various angular positions along a deflected recording medium, whereby the arrangement of chamber scraper, raster roller and developer roller relative to one another is sustained in the developer station. The printing module can additionally comprise a transfer roller that, for example, transfers the toner images from the image carrier element to the recording 25 medium.

Advantages of the ~~invention~~ preferred embodiment are:

- The the speed of the development can be flexibly adapted depending on the usage purpose, start, stop {sic} via feed of the liquid developer via the raster roller[.];
- 30 - The the simple design (for example only three rollers) enables a compact structural shape and therewith compact printing group designs[.]; and

- The the dosing ratio of a chamber scraper is largely viscosity-independent in a large range (0.5 – 1000 mPa*s) and ~~therewith~~ thus effects[[:]]
 - a stable processing of different concentrations of the liquid developer and ~~therewith~~ thus high process stability; and
 - the usage of identically-designed developer stations for different liquid developers (for example for different applications).

b) ~~The second problem to be solved is to specify a modularly-designed printing device with which a printing system can be achieved for the most varied, complex printing machines for professional, digital high-speed printing.~~

~~This problem is achieved according to the features of the claim 39.~~

As to the second problem, the The printing device for printing of a printing substrate is comprised of a combination of one or more printing groups with a common printing substrate guidance group as well as with a central control group for coordination of the workflows in the printing groups, in the printing substrate guidance group, as well as in possible connected apparatuses of the printing substrate pre- or post-processing.

The combination of essentially structurally identical (identical in cross-section arrangement, depth corresponding to that of the printing substrate width to be processed), compact and easily manipulable printing modules into a printing device with respectively different printing substrate guidance group, both for "Continuous ~~Feet~~ Feed" (printing on continuous printing substrate web) and for "Cut Sheet" (single sheet or, ~~respectively,~~ sheet printing), enables the flexible design of the most varied printing devices: from black-and-white (black/white) simplex to black-and-white duplex, YMCK (yellow, magenta, cyan, black) full color simplex to complex, full color duplex printers with four or more printing groups on each printing substrate side. In addition to the uncomplicated design of the complex printing devices at the manufacturer, the comparably easy retrofit and upgrade capability of existing

printing devices at the client is advantageous. The use of structurally-identical modules, in particular in the printing groups, additionally enables the cost-effective manufacture via large-scale manufacturing.

Advantageous properties of the printing groups and printing substrate group are:

- larger speed range (for example 0.3 to 3 m/s);
- printing substrate width advantageously up to at least 22 inches, however narrower is possible;
- variable speed during the running printing operation in the overall speed range;
- compact structural shape of the printing groups (for example (50x100) cm² cross-section, depth corresponding to printing substrate width); and
- easy handling capability of the printing groups given the installation and demounting in existing printing devices (retrofitting or, respectively, upgrading), if applicable via suitable auxiliary printing devices.

~~e) — The third problem to be solved by the invention is to specify an electrophotographic printing device and a method with which a variable speed can be realized given constant print quality.~~

~~This problem is solved with a printing device according to the features of the claim 72 and with a method with the features according to claim 101.~~

As to the third problem, the The printing device has the advantage that a change of the printing speed is possible in a continuously variable manner and in a large range without reduction of the print quality.

According to the invention preferred embodiment, a printing device is provided that is comprised of an image-generating system that generates an electronic charge image on an image carrier element (for example photoconductor), which electronic charge image is made visible by means of a developer station via charged ink particles (toner particles) and is subsequently transferred onto a recording medium or final image medium (for example paper) and fixed on this.

Given such a printing device it is possible

- to vary the speed of the image carrier element continuously from 0 to the limit speed;
- to adapt (with regard to information location and energy per area) the electronic character generation and, if applicable, the charge intensity of the speed of the image carrier element such that (for example in the electrographic process) the charge image (with regard to form and potential values) is always created in the same manner independent of the speed of the image carrier element; and
- to implement the development of the charge image with a charge image that allows it to develop the signal distribution on the image carrier element independent of its speed (in the electrographic process, this means that the same potential distributions on the image carrier element always generate the same toner distributions on the charge image during the development process).

For the case that the development of the charge image is not entirely independent of the speed of the image carrier element, the process parameters (for example photoconductor potential, light energy, auxiliary potential over the developer gap, toner concentration or, ~~respectively,~~ auxiliary potentials for transfer onto the final image medium) can be varied such that the toner image deposition on the image carrier element or, ~~respectively,~~ the final image medium is nearly identical given different velocity. The parameters to be influenced are advantageously to be coupled with one another via one or more regulatory processes.

A development method is advantageously used ~~the [sic]~~ that naturally generates an independent toner deposition up to the limit speed of the image carrier element. This occurs, for example, via a liquid development in which fine toner particles (advantageously approximately 1 μm in diameter or smaller) are dispersed in a high-ohmic carrier fluid (for example silicon oil), whereby the concentration of the toner particles can be selected so high that

so many toner particles are located in a thin developer gap (advantageously 5 to 10 μm) that the desired inking (optical density or, ~~respectively,~~ ink density) on the image carrier element is created given complete (or, ~~respectively,~~ nearly complete) deposition of all toner particles located in the developer gap.

5 It is furthermore a requirement for the function that the movement capability of the toner particles in the development gap is at least so large that, during the residence duration of the toner particles in the developer gap, all (or almost all) toner particles under the influence of the electrical field strength existing over the regions of the image carrier element to be inked completely traverse
10 the developer gap and are deposited on the regions to be inked on the surface of the image carrier element and, under the influence of the electrical field strength existing over the regions of the image medium that are not to be inked, are not or are nearly ~~[sic]~~ not, deposited on the surface of the image medium.

15 In this method, the respective achievable maximum inking can be pre-selected or set in connection with the targeted adjustment of the toner concentration in the developer fluid. In this printing process, a specifically set maximum inking can ~~therewith~~ thus be held constant given variable printing speed.

20 Such a developer station can comprise a developer roller that transports a liquid developer past the image carrier element such that the toner deposition on the image carrier element is independent of its speed.

The developer station can be executed such that[[,]]

- 25 - a developer roller is provided adjacent to the image carrier element, which developer roller directs the liquid developer comprising toner particles past the image carrier element and from which toner particles cross over to the image carrier element corresponding to the previously-generated charge images,
- 30 - a raster roller in whose rastering the liquid developer is transported to the developer roller is arranged adjacent to the developer roller,

- a chamber scraper comprising a dosing scraper is arranged adjacent to the raster roller, from which chamber scraper the raster roller accepts the liquid developer via the dosing scraper whose position relative to the raster roller is adjustable and that is designed such that the dosing scraper is overflowed by liquid developer.

The overflow can be achieved based on the gravitation of the liquid developer or via utilization of over-pressure.

It is advantageous that the quantity of the liquid developer transported by the raster roller can be established via the rastering of the raster roller. The transport of the liquid developer via the raster roller is ~~thereby~~ thus relative to the area and ~~therewith~~ thus independent of the print speed, such that the same quantity of liquid developer per areal unit is always directed to the developer roller given different printing speeds.

It is advantageous when the raster roller exhibits a rastering that enables the transport of a volume of liquid developer from 1 to 40 cm³/m² (corresponding to the roller surface), advantageously 5-20 cm³/m².

It is furthermore advantageous when the developer roller comprises an elastic coating that is in contact with the image carrier element and with the raster roller.

The chamber scraper can be a chamber situated on the circumferential surface of the raster roller, with two scrapers sealing the chamber, namely a closing scraper at the entrance of the chamber (viewed in the rotation direction of the raster roller), a dosing scraper at the exit of the chamber (viewed in the rotation direction of the raster roller), and with two seals laterally applied at the edge of the raster roller. The feed of the liquid developer into the chamber can ~~thereby~~ thus occur via one or more inlet openings, advantageously via pumping, and the removal of the liquid developer from the chamber can occur via inlet or outlet openings.

~~The various aspects of the invention that discretely and in combination represent the invention are described in the following using Figures.~~

~~Shown are:~~

Fig. 1 a representation of the developer station given a first position relative to the image carrier element;

Fig. 2 a representation of the developer station given a second position relative to the image carrier element;

5 Fig. 3 a representation of the developer station given a third position relative to the image carrier element;

Fig. 4 a representation of the developer station given different arrangement of the chamber scraper relative to the raster roller;

10 Fig. 5 a representation of print modules with developer stations around a recording medium;

Fig. 6 a single printing group that can be combined with a printing device as a module;

Fig. 7 a printing device for printing of endless printing substrate webs;

Fig. 8 a printing device for printing of individual sheets (cut sheet).

15 a) First aspect of the invention: device for transport of liquid developer to an image carrier element given electrophoretic digital printing

A) First Aspect of the Preferred Embodiment – A Device for Transport of Liquid Developer to an Image Carrier Element Given Electrophoretic Digital Printing

20 Design For design of a developer station E with the inventive feature according to Figure 1[[:]].

The the developer station E of Figure 4 comprises:

- a developer roller 203 with an elastic coating 206; multiple developer stations can also naturally be provided;
- 25 - a raster roller 202 with a rastering made up of depressions (cups) arranged thereupon; a plurality of raster rollers can also be provided; the rastering can be executed differently depending on the application case;
- a chamber scraper 201 that is variable in terms of its position
- 30 relative to the raster roller;
- a cleaning device with a cleaning roller 204 and a cleaning element 205.

The developer roller 203 contacts an image carrier element F, for example a photoconductor on a photoconductor belt or a roller with a photoconductor layer arranged thereupon. Furthermore, a transfer roller 121 (Fig. 5) can be provided for transfer of the toner image inked with fluid toner from the image carrier element F onto a belt-shaped recording medium 1 or, respectively, a sheet-shaped recording medium.

A liquid developer with ink means (toner particles) distributed therein, which liquid developer is suitable for electrophoretic development, can be used as it is known, for example, from EP 0 756 213 B1 or EP 0 727 720 B1.

The feed of the liquid developer for inking with toner particles of the image carrier element F according to the image occurs over the chamber scraper 201 and the raster roller 202 to the developer roller 203. The cleaning of the inverse residual image from the developer roller 203 in turn occurs via its transfer to the cleaning roller 204 and removal of the liquid developer from the cleaning roller 204 via a cleaning element 205 (for example a scraper). From the cleaning device 204, 205, the removed liquid developer can be transferred back to a reservoir for the liquid developer (not shown).

The developer roller 203, the raster roller 202, and the cleaning roller 204 rotate in an advantageous manner [sic] with constant speed ratios relative to one another (surface velocities), advantageously in a ratio of 1:1:1. The rotation direction of the developer roller 203 and of the medium element F can be in the same direction or in opposite directions; those of the developer roller 203 and of the raster roller 202 as well as of the developer roller 203 and of the cleaning roller 204 can be in the same direction or in opposite directions. Defined potentials for targeted field effect on the charged toner particles can be applied to them [sic].

The developer roller 203 has an elastic coating 206 and is in contact with the image carrier element F, with the raster roller 202 and with the cleaning roller 204.

The raster roller 202 is adapted in terms of its rastering for the transport of a volume of liquid developer from 1 to 40 cm³/m² (relative to the roller surface), advantageously 5-20 cm³/m².

The transport of liquid developer is additionally relative to the area and
5 therewith thus independent of the printing speed, i.e. the same quantity of liquid developer per areal unit of the developer roller 203 can always be supplied given different printing speeds.

The formation of defined effective zones for the transfer of liquid developer between developer roller 203 and image carrier element F,
10 developer roller 203₁ and cleaning roller 204 and developer roller 203 and raster roller 202 can be achieved in varying manners:

- via defined deformation of the elastic coating 206 of the developer roller 203, advantageously via elastic force delivery to adjacent elements such as, for example image carrier element
15 F, raster roller 202 or cleaning roller 204;
- via the incompressible layer of the liquid developer between developer roller 203 and image carrier element F, developer roller 203₁ and cleaning roller 204 or developer roller 203 and raster roller 202.

20 ~~Design and arrangement of the chamber scraper (201), in particular according to Fig. 4:~~

Design and Arrangement of the Chamber Scraper 201, in Particular According to Fig. 4

The chamber scraper 201 for offset printing is known from Kipphan,
25 Handbuch der Printmedien, Springer Verlag, 2000. Its use for electrophoretic digital printing given different positions of the developer station 200 relative to the image carrier element F results from Fig. Figs. 1 through 4.

The chamber scraper 201 is a chamber 207 situated on the circumferential surface of the raster roller 202, which chamber 207 is sealed
30 by two scrapers (the closing scraper R1 at the entrance of the chamber as viewed in the rotation direction of the raster roller 202 and the dosing scraper R2 at the exit of the chamber 207 as viewed in the rotation direction of the

raster roller 202) and two seals for sealing at the lateral edge of the raster roller 202 (not visible in the Figures). The feed of the liquid developer into the chamber 207 of the chamber scraper 201 can occur via one or more inlet openings, advantageously via pumping. The removal of the liquid developer
5 from the chamber 207 (for example advantageously for better mixing of the liquid developer) and the emptying of the chamber 207 can occur via either inlet or outlet openings.

An exchange of the inlet or outlet openings depending on the installation position of the chamber scraper 201 (Fig. 2, Fig. 3, Fig. 4) is
10 thereby possible (in Fig. 2 and 3, g designates the effective direction of gravity and therewith its influence on the liquid level in the chamber scraper 201).

The angular position of the chamber scraper 201 relative to the raster roller 202 is ~~thereby~~ thus limited in that the dosing scraper R2 must always be located below the surface of the liquid developer (this serves for air bubble-
15 free filling of the cups of the rastering of the raster roller 202).

The generation of slight over-pressure in the chamber scraper 201 can optionally be used in order to keep the dosing scraper R2 below the fluid surface. This solution is moreover suitable for processing of higher-viscosity liquid developer (for example 1000 mPa*s).

The installation positions of the chamber scraper 201 relative to the raster roller 202 are selectable, as Fig. 4 shows. The raster roller 202 together with the chamber scraper 201 can be arranged relative to the developer roller 203, depending on the installation position of the developer roller 203, such that the dosing scraper R2 is overflowed with liquid developer
20 (Fig. 1 through 4). The following embodiments are advantageous:

- one embodiment provides a constant angle between developer roller 203, cleaning roller 204 and raster roller 202 and enables an arrangement at various angles around the image carrier element F;
- an extension of the installation positions results via the additional possibility to vary the angular position of the chamber scraper 201 on the raster roller 202 (Fig. 4).

Fig. 5 shows an arrangement of a plurality of printing modules (PM), for example in a digital color printing device. Here printing modules PM, with an image carrier element F, a developer station (designated with E in Fig. 5) and a transfer roller 121 that transfers the toner image from the image carrier element F to a recording medium 1, are respectively arranged around the recording medium 1 that is deflected by a deflection roller 2. The design of the developer station E corresponding to ~~Fig.~~ Figs. 1 through 4 allows structurally identical printing modules PM to be arranged at various angles in the deflection region of the recording medium 1. This is in particular achieved via a usage of chamber scrapers 201 for feed of the liquid developer to the image carrier element F, since with this the use of the structurally identical developer stations E is possible at various installation positions (simplex, [sic] duplex, horizontal, vertical, angle range > 120° given satellite arrangement) of the printing device; see Fig. 5 for a digital color printing device with multiple developer stations E1 – E5 corresponding to the desired color separations. The angular range can ~~thereby~~ thus be carried via additional adjustable positions of the chamber scraper 201 (and of the cleaning device 204, 205) via an adjustment device or via adjustable design of chamber scraper 201 and cleaning device 204, 205 (Fig. 2, Fig. 3).

b) ~~Second aspect of the invention: - modularly designed printing device~~

B) Second Aspect of the Preferred Embodiment: - Modularly Designed Printing Device

In the following, as shown in Figs. 6 and 7, a printing system is comprised of a combination of multiple printing groups 100 arranged in succession with a common printing substrate guidance group 200. Machines of printing substrate pre- or, ~~respectively,~~ post-processing can be connected to the printing system. A central control group 400 for coordination of the workflows in the printing groups 100 and in the printing substrate guidance group 200 is additionally provided.

The printing groups 100 are executed as modules that can be combined with one another, which modules are structurally identical, compact

and easily manipulable. They can be adapted to the width of the printing substrate 1.

~~Design of an individual module = printing group 100~~

Design of an Individual Module = Printing Group 100

5 In the exemplary embodiment, the printing groups 100 are executed as electrographic printing groups as they are known, for example, from EP 0 727 720 B1. They comprise a printing unit 110 with an image generation element 111, a charge station 112, an image exposure station 113, a developer station 114 and an image generation element cleaning station 115. The image
10 generation element 111 can comprise a photoconductor such as a photoconductor drum or a photoconductor belt. The exposure station 113 can be an LED character generator or laser. The developer station 114 can be realized as an electrophoretic liquid developer station.

For example, the developer station 114 can comprise a developer roller
15 that transports a liquid developer past an image generation element 111 such that the toner deposition on the image generation element 111 is independent of its speed. A high-ohmic carrier fluid in which toner particles are dispersed can be provided as a liquid developer. ~~Example [sic]~~ An example of such a carrier fluid is silicon oil. The toner particles can advantageously exhibit a
20 diameter of approximately 1 μm .

The toner concentration in the liquid developer is additionally selected such that so many toner particles are located in the developer gap between developer roller and image generation element 111 that all or nearly all toner particles located in the developer gap create the desired inking of the charge
25 images given complete deposition. The developer gap should advantageously be 5 to 10 μm , and the mobility of the toner particles in the developer gap should advantageously be such that, during the residence duration of the toner particles in the developer gap, optimally all toner particles under the influence of the electrical field strength existing over the
30 image generation element 111 to be inked traverse the developer gap and are deposited on the surface of the image generation element 111 to be inked.

An advantageous developer station 114 can have the following design (Fig. 4):

- a developer roller 203 is arranged adjacent to the image generation element 111 (F), which developer roller 203 directs liquid developer comprising the toner particles past the image generation element 111 and from which developer roller 203 toner particles cross to the image generation element 111 (F) corresponding to the previously-generated charge images.
- A raster roller 202 is arranged adjacent to the developer roller 203, in the rastering of which raster roller 202 the liquid developer is transported to the developer roller 203.
- A chamber scraper 201 comprising a dosing scraper R2₁ is arranged adjacent to the raster roller 202, from which chamber scraper 201 the raster roller 202 accepts the liquid developer via the dosing scraper R2, the position of which chamber scraper 201 is adjustable relative to the raster roller 202 and which chamber scraper 201 is designed such that the dosing scraper R2 is overflowed by liquid developer.

The printing group 100 furthermore comprises a transfer unit 120 made up of a transfer element 121 (advantageously a transport roller or a transfer belt) and of a transfer printing station 123 with one or more rollers. The transfer printing station 123 can be combined with a transfer printing auxiliary means unit, advantageously with a corona device.

Furthermore, the transfer unit 120 can comprise a toner image conditioner station 122, advantageously a roller or a belt in contact with the transfer element 121 that, if applicable, can be electrically adjusted or tempered. The transfer unit 120 can additionally comprise a cleaning station 124 for cleaning of the transfer element 121 that, for example, is realized as a blade roller or fleece cleaner.

The printing group 100 furthermore comprises a printing group activation unit 130 with a power electronic electronics 131 and a digital electronics 132. The power electronic electronics 131 is associated

with the motor controllers and high voltage feeds of the printing unit 110 or, respectively, of the transfer unit 120; the digital ~~electronic~~ electronics 132 (for example a microprocessor controller) serves for realization of process regulations in cooperation with the central control group 400 (Fig. 7),
5 advantageously the signal processing including the interface controller to sensors of the printing unit 110 or, respectively, of the transfer unit 120.

The printing group 100 can additionally comprise an additional and auxiliary process unit 140 with an ink ~~means~~ feed station 141 and/or with a printing substrate conditioner station 142 (advantageously for paper
10 moistening) and/or with a filter and suction station 143 (advantageously for the developer station or for the corona device).

Finally, the printing group 100 comprises an image data processing unit 150 (a controller).

~~Design of the modularly designed printing device:~~

Design of the Modularly-Designed Printing Device

The design of a printing device for printing of a continuous printing substrate web ("continuous ~~feed~~" ~~[sic]~~ feed") results from Fig. 7. Here printing groups 100 are variably connected in series in the a number corresponding to the object to be fulfilled. The printing substrate guidance group (200) is
20 common to the printing groups 100. This printing substrate guidance group 200 comprises a printing substrate guidance unit 220 within the printing groups 100, a printing substrate web tension generation station 211 and/or a printing substrate web alignment station 212 and/or a printing substrate web extraction station 213.

The printing substrate web tension generation station 211 can be a negative pressure brake or an Omega draw that is arranged at the input of the printing system. The printing substrate web alignment station 212 can be realized as a pivoting frame that is likewise arranged at the input of the printing system. The printing substrate web extraction station 213 can be a
30 transport roller pair that is arranged at the output of the printing system.

At least one print image conditioner unit can be provided between the printing groups 100 and/or at the output of the printing system. Respectively

one unit for intermediate fixing 231 can be arranged as a print image conditioner unit between the printing groups 100; and a fixing station 232 (advantageously an IR radiation fixing or heat-pressure fixing) can be arranged at the output of the printing system. The unit for intermediate fixing
 5 or conditioning station 231 can, for example, also be omitted given a printing group 100 operating according to the electrophoretic principle.

Furthermore, a gloss station 233 can be provided at the output of the printing system.

To control the printing substrate guidance group 200, at least one
 10 electronic activation unit 240 is provided

- with a power ~~electronic~~ electronics 241, advantageously for motor controllers and high voltage supplies within the printing substrate guidance group 200,
- and/or with a digital ~~electronic~~ electronics 242 (for example
 15 microprocessor controller) for realization of the regulatory workflows for control or regulation of the printing substrate guidance in cooperation with the central control group 400 and/or for signal processing, including control of the interfaces to sensors of the printing substrate guidance group 200, the
 20 transfer printing unit(s) 123 as well as the print image conditioner units 231, 232, 233.

The design of the modular printing device for the printing of single sheets (cut sheet) can be learned from Fig. 8. In the following, only the components differing with regard to Fig. 7 are explained; the explanation
 25 regarding Fig. 7 is referred to for the identical components. It is thereby to be noted that identical associated reference characters exhibit a "3" at the beginning instead of a "2".

One difference with regard to Fig. 7 is to be seen in the printing substrate guidance group 300. This must be suitable for single sheet/sheet
 30 printing. The printing substrate guidance group 300 comprises a printing substrate guidance unit 310 with a transport belt 311 on which the individual sheets or sheets 1 rest and via which these are moved through the printing

system. Furthermore, an activation unit 340 is provided whose tasks correspond to those of the activation unit 240. This is referenced.

A central control group 400 is provided both in the printing device according to Fig. 7 and in Fig. 8. This central control group 400 comprises

- 5 - a central power ~~electronic~~ electronics 410,
- a central electronic printer activation unit 420.

The central activation unit 420 controls

- the interface to the printing substrate pre- and post-processing,
- and/or the interface to the printing groups 100,
- 10 - and/or the interface to the printing substrate guidance group 200 or 300,
- and/or the central printer controller for timely coordination of all workflows in the printing system as well as the entire printing path.

15 The central power ~~electronic~~ electronics 410 comprises a mains voltage switching and safety system as well as the central power supply of the printing system.

~~e) — Third aspect of the invention — electrographic printing device of variable printing speed~~

20 C) Third Aspect of the Preferred Embodiment Electrographic Printing Device of Variable Printing Speed

In the exemplary embodiment of Fig. 6, a printing group 100 is executed as electrographic printing groups as is known, for example, from EP 0 727 720 B1. It comprises a printing unit 110 with an image generation element 111, a charge station 112, an image exposure station 113, a
25 developer station 114 and an image generation element cleaning station 115. The image generation element 111 can comprise a photoconductor such as a photoconductor drum or a photoconductor belt. The exposure station 113 can be an LED character generator or laser. The developer station 114 can be realized as an electrophoretic liquid developer station according to Fig. 2.

30 The printing group 100 furthermore comprises a transfer unit 120 made up of a transfer element 121 (advantageously a transport roller or a transfer belt) and of a transfer printing station 123 with one or more rollers. The

transfer printing station 123 can be combined with a transfer printing auxiliary ~~means~~ unit, advantageously with a corona device.

Furthermore, the transfer unit 120 can comprise a toner image conditioner station 122, advantageously a roller or a belt in contact with the transfer element 121 that, if applicable, can be electrically adjusted or tempered. The transfer unit 120 can additionally comprise a cleaning station 124 for cleaning of the transfer element 121 that, for example, is realized as a blade roller or fleece cleaner.

The printing group 100 furthermore comprises a printing group activation unit 130 with a power ~~electronic~~ electronics 131 and a digital ~~electronic~~ electronics 132. The power ~~electronic~~ electronics 131 is associated with the motor controllers and high voltage feeds of the printing unit 110 or, ~~respectively,~~ of the transfer unit 120; the digital ~~electronic~~ electronics 132 (for example a microprocessor controller) serves for realization of process regulations in cooperation with the central control group 400, advantageously the signal processing including the interface controller to sensors of the printing unit 110 or, ~~respectively,~~ of the transfer unit 120.

The printing group 100 can additionally comprise an additional and auxiliary process unit 140 with an ink ~~means~~ feed station 141 and/or with a printing substrate conditioner station 142 (advantageously for paper moistening) and/or with a filter and suction station 143 (advantageously for the developer station or for the corona device).

Finally, the printing group 100 comprises an image data processing unit 150 (a controller).

The developer station E of Figure 4 comprises the following components:

- a developer roller 203 with an elastic coating 206
- a raster roller 202 with a rastering made up of depressions (cups) arranged thereupon; a plurality of raster rollers can also be provided; the rastering can be executed differently depending on the application case;

- a chamber scraper 201 that is variable in terms of its position relative to the raster roller;
- a cleaning device with a cleaning roller 204 and a cleaning element 205.

5 The developer roller 203 contacts an image carrier element F, for example a photoconductor on a photoconductor belt or a roller with a photoconductor layer arranged thereupon. The charge images that should be inked with toner particles are provided on the image carrier element F.

10 A liquid developer with ink ~~means~~ (toner particles) distributed therein, which liquid developer is suitable for electrophoretic development, can be used for said inking as it is known, for example, from EP 0 756 213 B1 or EP 0 727 720 B1. The liquid developer is transported by the developer roller 203 through a developer gap existing between image carrier element F and developer roller 203. There the toner particles cross over onto the image
15 carrier element F corresponding to the development method described above.

20 The feed of the liquid developer for inking with toner particles of the image carrier element F according to the image occurs over the chamber scraper 201 and the raster roller 202 to the developer roller 203. The cleaning of the inverse residual image from the developer roller 203 in turn occurs via its transfer to the cleaning roller 204 and removal of the liquid
25 developer from the cleaning roller 204 via a cleaning element 205 (for example a scraper). From the cleaning device 204, 205, the removed liquid developer can be transferred back to a reservoir for the liquid developer (not shown).

30 The developer roller 203, the raster roller 202 and the cleaning roller 204 rotate in an advantageous manner [~~sic~~] with constant speed ratios relative to one another (surface velocities), advantageously in a ratio of 1:1:1. The rotation direction of the developer roller 203 and of the medium element F can be in the same direction or in opposite directions; ~~these~~ directions of the developer roller 203 and of the raster roller 202 as well as of the developer
35 roller 203 and of the cleaning roller 204 can be in the same direction or in

opposite directions. Defined potentials for targeted field effect on the charged toner particles can be applied to them-~~[sic]~~.

5 The developer roller 203 has an elastic coating 206 and is in contact with the image carrier element F, with the raster roller 202₁ and with the cleaning roller 204.

10 The raster roller 202 is realized in terms of its rastering for the transport of a volume (adapted to the speed of the image carrier element F) of liquid developer of, for example, 1 to 40 cm³/m² (relative to the roller surface). The transport of liquid developer is relative to the area and ~~therewith~~ thus independent of the printing speed; this means that, given different printing speeds, the same quantity of liquid developer per areal unit of the developer roller 203 can always be supplied.

15 The formation of defined effective zones for the transfer of liquid developer between developer roller 203 and image carrier element F, developer roller 203₁ and cleaning roller 204 and developer roller 203 and raster roller 202 can be achieved in various manners:

- via defined deformation of the elastic coating 206 of the developer roller 203, advantageously via elastic force delivery to adjacent elements such as, for example image carrier element F, raster roller 202₁ or cleaning roller 204;
- via the incompressible layer of the liquid developer between developer roller 203 and image carrier element F, developer roller 203 and cleaning roller 204₁ or developer roller 203 and raster roller 202.

25 The developed charge images on the image carrier element F are finally transferred onto a recording medium directly or via a transfer roller. This process can occur in a known manner, for example as it is described in EP 0 727 720 B1.

30 While a preferred embodiment has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only the preferred embodiment has been shown and described and that all changes

MARKED-UP COPY

-25-

and modifications that come within the spirit of the invention both now or in the future are desired to be protected.

Reference list

- F ~~image carrier element~~
- PM ~~printing module~~
- E ~~developer station in the printing module PM~~
- 5 R1 ~~closing scraper of the chamber scraper~~
- R2 ~~dosing scraper of the chamber scraper~~
- 1 ~~recording medium, final image medium, printing substrate~~
- 2 ~~deflection roller~~
- 201 ~~chamber scraper~~
- 10 202 ~~raster roller~~
- 203 ~~developer roller~~
- 204 ~~cleaning roller~~
- 205 ~~cleaning element~~
- 206 ~~elastic coating of the developer roller~~
- 15 207 ~~chamber of the chamber scraper~~
- 300 ~~transfer roller~~
- 400 ~~printing group~~
- 110 ~~printing unit (for example electrographic printing unit)~~
- 111 ~~image generation element (for example photoconductor, OPC a-~~
- 20 ~~Si)~~
- 112 ~~charge station (for example corona device)~~
- 113 ~~image exposure station (for example LED character generator or~~
- ~~laser)~~
- 114 ~~developer station (for example electrophoretic liquid developer~~
- 25 ~~station)~~
- 115 ~~image generation element cleaning station (for example blade~~
- ~~rollers and/or fleece cleaner)~~
- 120 ~~transfer unit~~
- 121 ~~transfer element (for example transfer roller or transfer belt)~~
- 30 122 ~~toner image conditioner station (for example roller or belt in~~
- ~~contact with the transfer element, if applicable electrically~~
- ~~adjustable, if applicable temperable; corona device; IR heating)~~

MARKED-UP COPY

-27-

- 5 ~~123 transfer printing station (for example one or more rollers, if applicable combined with transfer printing auxiliary means such as corona devices, blades)~~
- 5 ~~124 transfer element cleaning station (for example blade, roller and/or fleece cleaner)~~
- 10 ~~130 power electronic (for example motor controllers and high voltage supplies)~~
- 10 ~~131 digital electronic (for example microprocessor controller (HW and SW) for realization of complex process regulations in cooperation with the central control group 400, if applicable signal processing including interfaces to sensors of the printing unit 110 or, respectively, the transfer unit 120)~~
- 15 ~~140 additional and auxiliary process unit~~
- 15 ~~141 ink means feed station (for example for the electrophoretic developer station)~~
- 15 ~~142 printing substrate conditioner station (for example for paper moistening)~~
- 20 ~~143 filter and suction station (for example for developer station or for corona devices)~~
- 20 ~~150 image data processing unit (controller)~~
- 20 ~~200 printing substrate guidance group for continuous printing substrate webs ("continuous feet" [sic])~~
- 25 ~~printing substrate tension generation station (for example negative pressure brake or Omega draw)~~
- 25 ~~printing substrate alignment station (for example pivot frames)~~
- 25 ~~printing substrate web extraction station (for example transport roller pair)~~
- 30 ~~220 printing substrate guidance unit~~
- 30 ~~221 transfer printing station (identical with 123)~~
- 30 ~~230 print image conditioner unit(s)~~

MARKED-UP COPY

-28-

- 231—intermediate conditioner station (for example intermediate fixing,
Si-oil reduction) fixer station (for example IR radiation fixing,
heat-pressure fixing) gloss station
- 240—electronic printing-substrate-guidance-group activation unit
- 5 241—power electronic (for example motor controllers and high voltage
supplies)
- 242—digital electronic (for example microprocessor controller (HW
and SW) for realization of the regulatory workflows for
control/regulation of the printing-substrate-guidance in
10 cooperation with the central control group 400, if applicable
signal processing including interfaces to sensors of the printing
unit 220 as well as of the print image conditioner units 230)
- 300—printing-substrate-guidance-group for single-sheet/sheet printing
("cut sheet")
- 15 310—printing-substrate-guidance unit
- 311—single sheet transport element (for example transport belt, if
applicable with defined set electrical conductivity)
- 320—transfer printing unit(s)
- 330—print image conditioner unit(s)
- 20 331—intermediate conditioner station (for example intermediate fixing,
Si-oil reduction)
- 332—fixer station (for example IR radiation fixing, heat-pressure
fixing)
- 333—gloss station
- 25 340—electronic printing-substrate-guidance-group activation unit
- 341—power electronic (for example motor controllers and high
voltage supplies)
- 342—digital electronic (for example microprocessor controller (HW
and SW) for realization of the regulatory workflows for
control/regulation of the printing-substrate-guidance in
30 cooperation with the central control group 400, if applicable
signal processing including interfaces to sensors of the printing

MARKED-UP COPY

-29-

~~substrate guidance unit 310, the transfer printing unit(s) 320 and
the print image conditioner units 330)~~

400—~~central control group~~

410—~~central power electronic~~

5 411—~~mains voltage switch and safety system~~

412—~~central power supply for printing groups and printing substrate
guidance group 200 or, respectively, 300~~

420—~~central electronic printer activation unit~~

~~Patent claims~~

WE CLAIM AS OUR INVENTION:

ABSTRACT OF THE DISCLOSURE

In a method or device for transport of liquid developer to an image carrier element for electrophoretic digital printing, a developer unit is arranged adjacent to the image carrier element, the developer unit directing a liquid developer comprising toner particles to the image carrier element, the toner particles crossing over to the image carrier element corresponding to previously-generated potential images. A raster unit is arranged adjacent to the developer unit. The raster unit transports the liquid developer to the developer unit by use of a raster. An electrical voltage is applied between the raster unit and the developer unit in order to exert a targeted field effect on the toner particles in a direction towards the developer unit. A chamber scraper comprising a dosing scraper is arranged adjacent to the raster unit and having liquid developer comprising said toner particles which are already charged. From the chamber scraper the raster unit accepts the liquid developer via the dosing scraper. The chamber scraper is arranged and operable such that the dosing scraper is washed over by the liquid developer.

10/565250

IAP20 Rec'd PCT/PTO 19 JAN 2006

Schaumburg Thoenes Thurn Landskron

New PCT Application

Case No. P05,0458 (26970-0402)

Client Ref. No. 2003-0704 PUS

5 Inventor: Berg et al.

Re.: Substitute pages with changes marked

10

Translation / 5 January 2006 / Bullock / 12950 words

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

Patent claims

1. Device for transport of liquid developer to an image carrier element given electrophoretic digital printing
- 5 a) in which a developer means (203) is arranged adjacent to the image carrier element (F), which developer means (203) directs a liquid developer comprising toner particles to the image carrier element (F) and from which developer means (203) toner particles cross over to the image carrier element (F) corresponding to the previously-generated potential images,
- 10 b) in which a raster means (202) is arranged adjacent to the developer means (203),
- in the rastering of which raster means (202) the liquid developer is transported to the developer means (203),
 - **an electrical voltage is applied between the raster means (202) and the**
- 15 **developer means in order to exert a targeted field effect on the toner particles in the direction towards the developer means,**
- c) in which a chamber scraper (201) comprising a dosing scraper (R2) is arranged adjacent to the raster means (202),
- which chamber scraper (201) comprises the liquid developer comprising
- 20 already-charged toner particles,
- from which chamber scraper (201) the raster means (202) accepts the liquid developer via the dosing scraper (R2)
 - which chamber scraper (201) is arranged and operable such that the dosing scraper (R2) is **washed over** by liquid developer.
- 25
2. Device according to claim 1,
- in which the chamber scraper (201) is arranged relative to the raster means (202) such that the dosing scraper (R2) is **washed over** by liquid developer due to gravity.

30

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

3. Device according to claim 1,
in which the liquid developer in the chamber scraper (201) is exposed to an over-
pressure such that the dosing scraper (R2) is **washed over** by liquid developer.
- 5 4. Device according to any of the claims 1 through 3,
in which a cleaning device (204, 205) is arranged adjacent to the developer means
(203) for removal from the developer means (203) of the liquid developer
comprising the inverse residual image, which cleaning device (204, 205) accepts
the residual image.
- 10 5. Device according to claim 4,
in which the cleaning device comprises a cleaning roller (204).
6. Device according to claim 5,
15 in which the liquid developer is stripped from the cleaning roller (204) by a
cleaning element (205), for example a scraper.
7. Device according to any of the claims 1 through 6,
in which the developer means (203) is a developer roller.
- 20 8. Device according to any of the preceding claims,
in which the raster means (202) is a raster roller.
9. Device according to claim 8,
25 in which the quantity of the liquid developer transported by the raster roller is
established by the rastering of the raster roller (202).
10. Device according to any of the claims 8 through 9,
in which the developer roller (203), raster roller (202) and cleaning roller (204)
30 rotate with constant speed ratios (surface velocities).

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

11. Device according to claim 10,
in which the developer roller (203), raster roller (202) and cleaning roller (204)
rotate in a ratio of 1:1:1.
- 5 12. Device according to any of the claims 7 through 11,
in which the movement directions of the surfaces of developer roller (203) and
image carrier element (F) are in the same direction or in opposing directions.
- 10 13. Device according to any of the claims 8 through 12,
in which developer roller (203) and raster roller (202) rotate in the same direction
or in opposing directions.
14. Device according to any of the claims 7 through 13,
15 in which the developer roller (203) and cleaning roller (204) rotate in the same
direction or in opposing directions.
15. Device according to any of the claims 7 through 14,
in which an electrical potential for targeted field effect on the charged toner
20 particles is respectively applied on developer roller (203) and image carrier
element (F).
16. Device according to any of the claims 7 through 15,
in which an electrical potential for targeted field effect on the charged toner
25 particles is applied on developer roller (203) and cleaning roller (204).
17. Device according to any of the claims 7 through 16,
in which the developer roller (203) comprises an elastic coating (206) that is in
contact with the image carrier element (F), with the raster roller (202) and with the
30 cleaning roller (204).

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

18. Device according to any of the claims 8 through 17,
in which the transport of the liquid developer by the raster roller (202) is relative to
the area and therewith independent of the printing speed, such that the same
5 quantity of liquid developer per areal unit is always directed to the developer roller
(203) given different printing speeds.

19. Device according to claim 18,
in which the raster roller (202) exhibits a rastering that enables the transport of a
10 volume of liquid developer from 1 to 40 cm³/m² (dependent on the roller surface),
advantageously 5-20 cm³/m².

20. Device according to any of the claims 8 through 19,
in which the developer roller (203) and the image carrier element (F) or,
15 respectively, the developer roller (203) and the cleaning roller (204) or,
respectively, the developer roller (203) and the raster roller (202) are arranged
relative to one another such that defined effective zones **in which liquid developer
migrates** form for the liquid developer.

20 21. Device according to claim 20,
in which the effective zone is formed via a defined deformation of the elastic
coating (206) of the developer roller (203), advantageously via elastic force
delivery to the adjacent elements (image carrier element (F); cleaning roller (204);
raster roller (202)).

25
22. Device according to claim 20,
in which an incompressible layer of the liquid developer establishes the separation
between developer roller (203) and image carrier element (F) or, respectively,
developer roller (203) and cleaning roller (204) or, respectively, developer roller
30 (203) and raster roller (202).

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

23. Device according to any of the claims 8 through 22,
in which the chamber scraper (201) comprises a chamber (207) situated on the
circumferential surface of the raster roller (202), two scrapers (R1, R2) – one
5 closing scraper (R1) at the entrance of the chamber (207) as viewed in the rotation
direction of the raster roller (202), one dosing scraper (R2) at the exit of the
chamber (207) as viewed in the rotation direction of the raster roller (202) –
sealing the chamber (207), and two seals laterally situated on the edge of the raster
roller (202).
10
24. Device according to claim 23,
in which the feed of the liquid developer into the chamber (207) occurs via one or
more inlet openings, advantageously via pumping.
- 15 25. Device according to claim 23 or 24,
in which the removal of the liquid developer from the chamber (207) occurs via
inlet or outlet openings.
26. Device according to claim 25,
20 in which the inlet or outlet openings can be exchanged depending on the
installation position relative to the raster roller (202).
27. Device according to any of the claims 23 through 26,
in which the angular position of the chamber scraper (201) relative to the raster
25 roller (202) is limited in that the dosing scraper (R2) is located below the surface of
the liquid developer in the chamber (207).
28. Device according to any of the claims 23 through 27,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

in which the processing of a higher-viscosity liquid developer (for example 1000 mPa*S) is made easier via generation of a slight over-pressure in the chamber (207).

- 5 29. Device according to any of the claims 23 through 28,
in which the installation position of the chamber scraper (201) on the raster roller
(202) is variable.
30. Device according to any of the claims 23 through 29,
10 in which the installation position of the cleaning device (204, 205) on the
developer roller (203) is variable.
31. Electrophoretic printing device,
in which at least one device (developer station E) according to any of the claims 1
15 through 30 is provided for development of potential images on the image carrier
element (F).
32. Electrophoretic printing device according to claim 31,
in which the developer roller (203), the raster roller (202) and the cleaning roller
20 (204) are arranged in the developer station (E) at a constant angle relative to one
another, such that the arrangement of developer stations (E) around the image
carrier element (F) at various angular positions is possible without changing the
association of developer roller (203), raster roller (202), cleaning roller (203 [sic])
relative to one another.
- 25 33. Electrophoretic printing device according to claim 31 or 32,
- in which printing modules (PM) respectively made up of a developer
station (E) and an image carrier element (F) are provided,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

- in which the developer roller (203), the raster roller (202) and the cleaning roller (204) are arranged in the developer station (E) at a constant angle relative to one another,
- in which the printing modules (PM) are arranged at various angular positions along a deflected recording medium (1), whereby the arrangement of chamber scraper (201), raster roller (202) and developer roller (203) relative to one another is maintained in the respective developer station (E).

in which a transfer roller (121) is arranged in the printing module between image carrier element (F) and recording medium (1).

35. Electrophoretic printing device according to claim 32, 33 or 34, in which the angular position of the developer stations (E) relative to the image carrier element (F) or, respectively, of the printing modules (PM) relative to the recording medium (1) can additionally be expanded by the possibility that the angular position of the chamber scraper (201) on the raster roller (202) is variable.

36. Electrophoretic printing device according to any of the claims 31 through 35, in which a plurality of developer stations (E) can be arranged in a digital color printing device.

37. Electrophoretic printing device according to any of the claims 31 through 36, in which identically designed developer stations (E1 – E5) can be used for different developer fluids (for example for different applications).

38. Method for transport of liquid developer to an image carrier element in electrophoretic digital printing,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

in which the feed of the liquid developer to the image carrier element (F) occurs via a device according to the claims 1 through 30.

39. Modularly-designed printing device that is suitable for realization of a
5 design of the most varied, complex printing machines for professional digital high-speed printing,
- in which a printing system made up of a combination of a plurality of printing groups (100) that can be operated **independent of one another** is provided with a printing substrate guidance group (200, 300) that is common to the
10 printing groups, **via which printing substrate guidance group (200, 300) a printing substrate is transported through the printing system,**
 - in which the printing groups comprise, respectively, one printing unit (110) for printing of the printing substrate, respectively one printing group activation unit (130) for control of the printing operation of the printing unit,
15 and respectively one image data unit (150) for preparation of the image data to be printed,
 - in which the printing substrate guidance group (200, 300) comprises a printing substrate guidance unit (220) for transport of the printing substrate through the printing system and an activation unit (240) for control of the
20 operation of the printing substrate guidance unit (200, 300),
 - in which a central control group (400) for **synchronization** of the workflows in the printing groups (100) and in the printing substrate guidance group (200, 300) is provided, **whereby the central control group (400) comprises interfaces to the printing groups (100) and to the printing substrate**
25 **guidance group (200, 300),**
 - in which machines of the printing substrate pre- or, respectively, post-processing are connected before the printing system or, respectively, after the printing system.

- 30 40. Printing device according to claim 39,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

in which the printing groups (100) are executed as modules that can be combined with one another that are structurally identical, compact and easily manipulable.

41. Printing device according to claim 39 or 40,
5 in which the printing groups (100) can be adapted to the width of the printing substrate (1).

42. Printing device according to claim 39, 40 or 41,
10 in which the printing groups (100) are executed as electrographic printing groups.

43. Printing device according to claim 42,
in which a printing group (100) respectively comprises a printing unit (110) with an image generation element (111), a charge station (112), an image exposure station (113), a developer station (114) and an image generation element cleaning
15 station (115).

44. Printing device according to claim 43,
in which the image generation element (111) comprises a photoconductor such as a photoconductor drum, a photoconductor belt.
20

45. Printing device according to claim 43 or 44,
in which the exposure station (113) is an LED character generator or a laser.

46. Printing device according to any of the claims 43 through 45,
25 in which the developer station (114) is an electrophoretic liquid developer station.

47. Printing device according to claim 46,
in which the developer station (114) comprises a developer roller (202) that transports a liquid developer past the image generation element (111) such that the
30 toner deposition on the image generation element (111) is independent of its speed.

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

48. Printing device according to claim 47,
in which a high-ohmic carrier fluid in which toner particles are dispersed is
provided as a liquid developer.

5

49. Printing device according to claim 48,
in which the carrier fluid is silicon oil.

50. Printing device according to any of the claims 46 through 49 with a
10 developer station

- in which a developer roller (203) is arranged adjacent to the image carrier
element (111), which developer roller (203) directs a liquid developer comprising
toner particles to the image carrier element (111) and from which developer roller
(203) toner particles cross over to the image carrier element (111) corresponding to
15 the previously-generated potential images,

- in which a raster roller (202) in whose rastering the liquid developer is
transported to the developer roller (203) is arranged adjacent to the developer roller
(203),

- in which a chamber scraper (201) comprising a dosing scraper (R2) is
20 arranged adjacent to the raster roller (202), from which chamber scraper (201) the
raster roller (202) accepts the liquid developer via the dosing scraper (R2) whose
position relative to the raster roller (202) is adjustable, and which chamber scraper
(201) is designed such that the dosing scraper (R2) is **washed over** by liquid
developer.

25

51. Printing device according to any of the claims 39 through 50,
in which the printing group (100) respectively comprises a transfer unit (120)

- with a transfer element (121), advantageously with a transfer roller or a
transfer belt,

30 - with a transfer printing station (123) with one or more rollers.

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and
italicized are to be deleted.

52. Printing device according to claim 51,
in which the transfer printing station (123) is combined with transfer printing
auxiliary means, advantageously with a corona device.

5

53. Printing device according to claim 51 or 52,
in which the transfer unit (120) comprises a toner image conditioner station (122),
advantageously a roller or a belt in contact with the transfer element (121), if
applicable electrical adjustable or temperable.

10

54. Printing device according to any of the claims 51 through 54,
in which the transfer unit (120) comprises a cleaning station (124) for cleaning of
the transfer element (121), which cleaning station (124) comprises a blade, roller
or fleece cleaner.

15

55. Printing device according to any of the claims 39 through 54,
in which the printing group (100) comprises a printing group activation unit (130),
- with a power electronic (131) that is associated with the motor controllers
and high voltage supplies of the printing unit (110) or, respectively, transfer unit
20 (120),
- with a digital electronic (132, for example microprocessor controller) for
realization of process regulations in cooperation with the central control group
(400), advantageously of signal processing including the interface controller for
sensors of the printing unit (110) or, respectively, the transfer unit (120).

25

56. Printing device according to any of the claims 39 through 55,
in which the printing group (100) comprises an additional and auxiliary process
unit (140),
- with an ink means feed station (141),

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and
italicized are to be deleted.

- and/or with a printing substrate conditioner station (142), advantageously for paper moistening,
- and/or with a filter and suction station (143), advantageously for the developer station or for the corona device.

5

57. Printing device according to any of the claims 39 through 56, in which the printing group (100) comprises an image data processing unit (150, controller).

10 58. Printing device according to any of the claims 39 through 57, in which the printing substrate guidance group (200) is suitable for continuous printing substrate webs ("continuous feet" [sic]),

- with a printing substrate web tension generation station (211),
- and/or with a printing substrate web alignment station (212),
- 15 - and/or with a printing substrate web extraction station (213).

59. Printing device according to claim 58, in which the printing substrate web tension generation station (211) is a negative pressure brake or an Omega draw that is arranged at the input of the printing
20 system.

60. Printing device according to claim 58 or 59, in which the printing substrate web alignment station (212) is a pivoting frame that is arranged at the input of the printing system.

25

61. Printing device according to any of the claims 58 through 60, in which the printing substrate web extraction station (213) is a transport roller pair that is arranged at the output of the printing system.

30 62. Printing device according to any of the claims 39 through 61,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

in which at least one print image conditioner unit (230) is provided.

63. Printing device according to claim 62,
in which respectively one unit for intermediate fixing (231) is arranged as a print
5 image conditioner unit between the printing groups (100).

64. Printing device according to claim 62 or 63,
in which a fixing station (232) (advantageously an IR radiation fixing or heat-
pressure fixing) is provided at the output of the printing system.

10

65. Printing device according to any of the claims 39 through 64,
in which a gloss station (233) is provided at the output of the printing system.

66. Printing device according to any of the claims 39 through 65,
15 in which the printing substrate guidance group (200) comprises at least one
electronic activation unit (240)
- with a power electronic (241), advantageously for motor controllers and
high voltage supplies,
- and/or with a digital electronic (242, for example microprocessor
20 controller) for realization of the regulatory workflows for control or regulation of
the printing substrate guidance in cooperation with the central control group (400)
and/or for signal processing, including control of the interfaces to sensors of the
printing substrate guidance group (200), the printing substrate guidance units (220)
including the transfer printing unit(s) (221) as well as the print image conditioner
25 units (230).

67. Printing device according to any of the claims 39 **through 57 and 62**
through 66,
in which at least one printing substrate guidance group (300) for single sheet/sheet
30 printing is provided.

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

68. Printing device according to claim 67,
in which the printing substrate guidance group (300) for single sheet/sheet
printing comprises a transport belt (311) on which the individual sheets or
5 sheets rest.

69. Printing device according to any of the claims 39 through 68,
in which a central control group (400) is provided.

- 10 70. Printing device according to claim 69,
in which the central control group (400) comprises
- a central power electronic (410),
 - at least one central electronic printer activation unit (420).
 - and/or an interface (421) to the printing substrate pre- and post-processing,
 - 15 - and/or an interface (422) to the printing groups (100),
 - and/or an interface (424) to the printing substrate guidance group (200 or
300),
 - and/or the central printer controller (425) for timely coordination of all
workflows in the printing system as well as the entire printing path.

20

71. Printing device according to claim 70,
in which the central power electronic (410) comprises a mains voltage switching
and safety system as well as the central power supply of the printing system.

- 25 72. Electrographic printing device comprised of an image generating system
that generates an electrical charge image on an image carrier element, which
electronic charge image is made visible by means of a developer station via
charged ink particles (toner particles) and is subsequently transferred onto a final
image medium and fixed on this, in which **means are provided in order to be**

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and
italicized are to be deleted.

able to continuously vary the speed of the image carrier element (F) from 0 up to a limit speed,

- which means adapt the charge intensity of the image carrier element (F) to its speed,

5 - which means adapt the exposure intensity in the exposure according to the image and in the deletion exposure of the image carrier element (F) to its speed,

- which means keep the supply of toner to the image carrier element (F) constant per area.

10

73. Printing device according to claim 72,

in which the charge intensity is adapted with regard to the speed of the image carrier element (F).

15 74. Printing device according to claim 72 or 73,

in which the electronic character generation is adapted to the speed of the image carrier element (F) with regard to the information location and energy per area, such that in the electrographic process the charge image (with regard to form and potential values) is always created in the same manner independent of the speed of
20 the image carrier element (F).

75. Printing device according to any of the claims 72 through 74,

in which the developer station is designed such that the signal distribution on the image carrier element (F) is developed independent of its speed, such that during
25 the development process identical potential distributions on the image carrier element (F) always generate the same toner distributions on the charge images.

76. Printing device according to claim 75,

in which the process parameters (such as photoconductor potential, light energy,
30 auxiliary potential across the developer gap, toner concentration) are variable for

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

the case that the development of the charge image is not entirely independent of the speed of the image carrier element (F), such that the toner image deposition on the image carrier element (F) is nearly identical at different speeds.

5 77. Printing device according to any of the claims 72 through 76,
in which the process parameters (such as auxiliary potential between image carrier
element (F) and final image medium (1), between image carrier element (F) and
intermediate carrier, between intermediate carrier and final image medium (1)) are
variable for the case that the transfer of the toner image onto the final image
10 medium (1) directly or, respectively, via an intermediate carrier is not entirely
independent of the speed of the image carrier element (F), such that the toner
image deposition on the image carrier element (F) is nearly identical at different
speeds.

15 78. Printing device according to claim 76 or 77,
in which the process parameters to be influenced are coupled with one another via
one or more regulatory processes.

79. Printing device according to any of the claims 72 through 78,
20 in which the inking of the image medium (F) by the developer station occurs
according to the electrophoretic principle.

80. Printing device according to claim 79,
in which a developer roller (203) is provided in the developer station (200), which
25 developer roller (203) transports a liquid developer past the image carrier element
(F) such that the toner deposition in the image carrier element (F) is independent of
its speed.

81. Printing device according to claim 80,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

in which a high-ohmic carrier fluid in which toner particles are dispersed is provided as a liquid developer.

82. Printing device according to claim 81,
5 in which the carrier fluid is silicon oil.

83. Printing device according to claim 81 or 82,
in which the toner particles advantageously exhibit a diameter of approximately 1
µm.

10 84. Printing device according to any of the claims 72 through 83,
in which the toner concentration in the liquid developer is selected such that so
many toner particles are located in the developer gap between developer roller
(203) and image carrier element (F) that all toner particles located in the developer
15 gap create the desired inking of the charge images given complete deposition.

85. Printing device according to claim 84,
in which the developer gap is advantageously 5 to 10 µm.

20 86. Printing device according to claim 84 or 85,
in which the mobility of the toner particles in the developer gap is such that, during
the residence duration of the toner particles in the developer gap, *optimally* all
toner particles under the influence of the electrical field strength existing over the
image carrier element to be inked traverse the developer gap and are deposited on
25 the surface of the image carrier element to be inked.

87. Printing device according to any of the claims 72 through 86 with a
developer station
- in which a developer roller (203) is arranged adjacent to the image carrier
30 element (F), which developer roller (203) directs liquid developer comprising the

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

toner particles past the image carrier element (F) and from which developer roller (203) toner particles cross over to the image carrier element (F) corresponding to the previously-generated charge images,

- in which a raster roller (202) is arranged adjacent to the developer roller (203), in the rastering of which raster roller (202) the liquid developer is transported to the developer roller (203),
- in which a chamber scraper (201) comprising a dosing scraper (R2) is arranged adjacent to the raster roller (202), from which chamber scraper (201) the raster roller (202) accepts the liquid developer via the dosing scraper (R2), the position of which chamber scraper (201) is adjustable relative to the raster roller (202) and which chamber scraper (201) is designed such that the dosing scraper (R2) is overflowed by liquid developer.

88. Printing device according to claim 87,
in which the chamber scraper (201) is arranged relative to the raster roller (202) such that the dosing scraper (R2) is **washed over** by liquid developer due to gravity.

89. Printing device according to claim 87 or 88,
in which the liquid developer in the chamber scraper (201) is exposed to an over-pressure such that the dosing scraper (R2) is **washed over** by liquid developer.

90. Printing device according to any of the claims 80 through 89,
in which a cleaning device (204, 205) is arranged adjacent to the developer roller (203) for removal from the developer roller (203) of the liquid developer comprising the inverse residual image, which cleaning device (204, 205) accepts the residual image.

91. Printing device according to claim 90,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

in which the cleaning device comprises a cleaning roller (204) and a cleaning element (205), for example a scraper, that strips the liquid developer from the cleaning roller.

- 5 92. Printing device according to any of the claims 87 through 91,
in which the transport of the liquid developer by the raster roller (202) is relative to the area and therewith independent of the printing speed, such that the same quantity of liquid developer per areal unit is always directed to the developer roller (203) given different printing speeds.

10

93. Printing device according to claim 92,
in which the quantity of the liquid developer transported by the raster roller is established by the rastering of the raster roller (202).

- 15 94. Printing device according to claim 93
in which the raster roller (202) exhibits a rastering that enables the transport of a volume of liquid developer from 1 to 40 cm³/m² (dependent on the roller surface).

95. Printing device according to any of the claims 87 through 94,
20 in which the developer roller (203), raster roller (202) and cleaning roller (204) rotate with constant speed ratios (surface velocities).

96. Printing device according to claim 95,
in which the developer roller (203), raster roller (202) and cleaning roller (204)
25 rotate in a ratio of 1:1:1.

97. Printing device according to any of the claims 87 through 96m
in which the developer roller (203) comprises an elastic coating (206) that is in contact with the image carrier element (F), with the raster roller (202) and with the
30 cleaning roller (204).

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

98. Printing device according to any of the claims 87 through 97,
in which the chamber scraper (201) comprises a chamber (207) situated on the
circumferential surface of the raster roller (202), two scrapers (R1, R2) – one
5 closing scraper (R1) at the entrance of the chamber (207) as viewed in the rotation
direction of the raster roller (202), one dosing scraper (R2) at the exit of the
chamber (207) as viewed in the rotation direction of the raster roller (202) –
sealing the chamber (207), and two seals laterally situated on the edge of the raster
roller (202).

10

99. Printing device according to claim 98,
in which the feed of the liquid developer into the chamber (207) occurs via one or
more inlet openings, advantageously via pumping.

15 100. Printing device according to claim 98 or 99,
in which the removal of the liquid developer from the chamber (207) occurs via
inlet or outlet openings.

20 101. Method for operation of an electrophotographic printing device with
variable printing speed using a printing device according to the claims 72 through
99.

25 102. Method according to claim 101,
in which the electronic character generation is adapted to the speed of the image
carrier element (F) such that, in the electrographic process, the charge image (with
regard to form and potential values) is always created in the same manner
independent of the speed of the image carrier element (F).

103. Method according to claim 101 or 102,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and
italicized are to be deleted.

in which the charge intensity is adapted (with regard to information location and energy per area) to the speed of the image carrier element (F).

104. Method according to any of the claims 101 through 103,
5 in which the developer station is designed such that the signal distribution on the image carrier element (F) is developed independent of its speed, such that during the development process identical potential distributions on the image carrier element (F) always generate the same toner distributions on the charge images.
- 10 105. Method according to claim 104,
in which the process parameters (such as photoconductor potential, light energy, auxiliary potential across the developer gap, toner concentration) are varied for the case that the development of the charge image is not entirely independent of the speed of the image carrier element (F), such that the toner image deposition is
15 nearly identical given different speeds of the image carrier element (F).
106. Method according to any of the claims 101 through 105,
in which the process parameters (such as auxiliary potential between image carrier element (F) and final image medium, between image carrier element (F) and
20 intermediate carrier, between intermediate carrier and final image medium) are varied for the case that the transfer of the toner image onto the final image medium (1) directly or, respectively, via an intermediate carrier is not entirely independent of the speed of the image carrier element (F), such that the toner image deposition on the final image medium is nearly identical at different speeds.
25
107. Method according to claim 105 or 106,
in which the process parameters to be influenced are coupled with one another via a regulatory process or a plurality of regulatory processes.
- 30 108. Method according to any of the claims 101 through 107,

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.

in which the potential images on the image carrier element (F) are developed according to the electrophoretic principle.

109. Method according to claim 108,

- 5 in which a developer roller (203) in the developer station (E) transports a liquid developer past the image carrier element (F) such that the toner deposition in the image carrier element (F) is independent of its speed.

110. Method according to claim 109,

- 10 in which the toner concentration in the liquid developer is selected such that so many toner particles are located in the developer gap between developer roller (203) and image carrier element (F) that the desired inking of the charge images is created given complete deposition of all toner particles located in the developer gap.

15

111. Printing device according to claim 109 or 110,

- in which the mobility of the toner particles in the developer gap is such that, during the residence duration of the toner particles in the developer gap, optimally all toner particles under the influence of the electrical field strength existing over the
20 image carrier element to be inked traverse the developer gap and are deposited on the surface of the image carrier element (F) to be inked.

SUBSTITUTE PAGES WITH CHANGES MARKED

Passages marked in bold face are additions or substitutions. Passages underlined and italicized are to be deleted.